Metered Feed Fertilizer Spreaders

- Metered feed measures fertilizer accurately
- Fertilizer flow stops and starts with the spreader
- Agitator breaks up lumpy material but does not pulverize pellets
- Machine can be cleaned and reassembled in a few minutes
- Entire bottom can be removed for easy cleaning
- · Fertilizer stays in place even on the steepest of hills
- · Weight is centered on spreader to keep even load on tongue

Hopper Specifications	36′	45′
Weight (lbs)	4,200	6,500
Height	54"	73"
Length (folded)	29'	31'
Width (folded)	8'	10'
Hopper Capacity (lbs)	6,500	10,000
Recommended Tire Size	16.5L x 16.1"	21.5L x 16.1"

Hopper Material 14 gauge mild or #304 stainless steel

Drive System Spreader clutch can be controlled from tractor

Standard Features Stainless steel housings, waterproof lids, agitator shields, clevis hitch,

hydraulic clutch and fill auger on 45'

Optional Features Acre tally, chemical feed screw and hydraulic fold on 45'

Barber Engineering Company manufactures dry fertilizer spreaders and nurse boxes. Strict adherence to original Barber designs and quality workmanship make the products you receive the finest available.

Additionally, replacement parts are manufactured by Barber and are usually in stock and ready for immediate shipment.

Specifications subject to change without notice.



1404 N. Regal • Spokane, WA 99202 (509) 535-3051

Fax (509) 534-6231



Barber... Better Built

Fertilizer Spreaders