Low-Profile Nurse Box

- Side discharge one-piece folding auger
- Choose mild or stainless steel welded design
- Mild steel unit has powder coated finish
- Easily handles fertilizer, grain and seed products
- Flatbed mount, low center of gravity

Specifications	12′	16′	20′
Hopper Dimensions	7' x 12'	7' x 16'	7' x 20'
Overall Height	64"	64"	64"
Overall Height with 10" Higher Sides	74"	74"	74"
Weight (lbs)	2300	3100	3900
Hopper Capacity (cu ft)	204	272	340
Hopper Capacity with 10" Higher Sides (cu ft)	274	365	457
Auger Dimensions	8" x 12' 8" x 14'	8" x 12' 8" x 14'	8" x 12' 8" x 14'
Discharge Height (from box frame)	12' auger - 7' 14' auger - 8' 8"	12' auger - 7' 14' auger - 8' 8"	12' auger - 7' 14' auger - 8' 8"
Raised Auger Overhang	12' auger - 5' 4" 14' auger - 7'	12' auger - 5' 4" 14' auger - 7'	12' auger - 5' 4" 14' auger - 7'
Lowered Auger Overhang	12' auger - 40" 14' auger - 64"	12' auger - 16" 14' auger - 40"	12' auger - 0" 14' auger - 16"
Compartments	2	3	4

Hopper Material 12 gauge mild or #304 stainless steel

Drive System Truck hydraulics or self contained hydraulic system including 18HP gas engine,

oil tank and battery

Standard Features Vinyl tarp, tarp tie-downs, three section stainless steel downspout, forklift bars,

stainless steel cross auger housing and auger cleanout gate

Optional Features Roll tarp and 10" higher sides

Barber Engineering Company manufactures dry fertilizer spreaders and nurse boxes. Strict adherence to original Barber designs and quality workmanship make the products you receive the finest available.

Additionally, replacement parts are manufactured by Barber and are usually in stock and ready for immediate shipment.

Specifications subject to change without notice.



1404 N. Regal • Spokane, WA 99202 (509) 535-3051

Fax (509) 534-6231





Nurse Boxes



