C-200 Cleaner & Slurry Treater

- Roll feed hopper measures grain and slurry while grading grain by size and weight
- Elevator, treater and slurry tank are easily removed for cleaning
- Precision gear box on bottom of bulking elevator
- Moving rack bar under lower screen keeps screen clean at all times
- Automatic slurry metering device, screening bagger
- Roll feed hopper clutch stops flow of seed and slurry without stopping machine
- Lever controlled variable speed pulley on fan and roll feed hopper

Specifications

Capacity	200 bushels per hour
Length	56"
Width	72"
Height	63"
Length of Elevating Auger	12'
Discharge Height	100"

Construction Welded steel frame

Drive System 1 1/2 HP electric motor, v-belt driven

Standard Features Three upper round hole scalping screens, 1/4, 5/16 and 3/8 one 1/2 x 11 lower

wire screen

Optional Features 15' elevator with discharge height of 122"

Barber Engineering Company manufactures dry fertilizer spreaders and nurse boxes. Strict adherence to original Barber designs and quality workmanship make the products you receive the finest available.

Additionally, replacement parts are manufactured by Barber and are usually in stock and ready for immediate shipment.

Specifications subject to change without notice.



1404 N. Regal • Spokane, WA 99202 (509) 535-3051

Fax (509) 534-6231



Barber...
Better Built





